



AR 210

BRIEF DESCRIPTION	AR 210 is an effective remover of shadows and residual paint.
APPLICATIONS	Removes paint residues and residual shadows after use of the ALL REMOVE Graffiti Removers . Care is required in the case of painted surfaces and plastic surfaces.
PROCESSING	<ul style="list-style-type: none">- Pour on undiluted above the shadow to be removed. (Do not spray or brush on).- Allow to act for 1 to 10 minutes.- Wash off thoroughly with water (better results are obtained if hot water is used).- If the paint shadows to be removed cannot be removed completely with the first application, then repeat the above treatment several times.- Always thoroughly wet the surface lower down.- After using the AR 210, the surface must be neutralised. To do this, either use a product with a pH of 4 or thoroughly rinse the surface with cold water.
BIODEGRADABILITY ACCORDING TO DIN 38412/OECD 301 D	93.4% within 15 days
CONTENT	Contains > 5% of alkali metal hydroxide
pH value	14 (highly alkaline)
TECHNICAL SAFETY MEASURES	Store in a cool, dry place. Keep away from children. Tightly close opened containers. Ensure thorough ventilation during use. Do not smoke, do not work near an open flame.
PERSONAL PROTECTIVE EQUIPMENT	Wear gloves (of butyl rubber) and eye protection (safety goggles). When using large amounts, wear respiratory protection with filter A.
WORK HYGIENE	The usual precautions for handling chemicals must be observed. <ul style="list-style-type: none">- AR 210 is highly corrosive; in case of contact with the skin, wash off with soap and water.- Do not take internally, toxic when swallowed.- Splashes in the eyes should be thoroughly washed out with water and a doctor consulted.

The information given in this technical data sheet is based upon our present knowledge and experience. Because of the wide variety of possible influences during processing and in the use of our products, it is the responsibility of the processor to carry out himself the necessary tests and trials on site. No legally binding guarantees for certain properties nor the suitability for a concrete application can be derived from the technical data sheet. Existing laws and regulations must be complied with by processors of our products on their own responsibility.

PSS INTERSERVICE U.K. LIMITED

Unit K2 Prospect Court, Prospect Close
Lowmoor Business Park
Kirkby-in-Ashfield, Notts NG17 7LF
Tel: ++44-1623-750 222
Fax: ++44-1623-723 222

<http://www.pss-technology.co.uk>
e-mail : info@pss-technology.co.uk

PSS INTERSERVICE LTD .

European Headquarter

Rebbergstr. 10
P.O. Box
CH-8954 Geroldswil
Tel: ++41-1-749 24 24
Fax: ++41-1-749 24 25

<http://www.pss-technology.com>
e-mail : info@pss-technology.com