



AR 728

- PRODUCT DESCRIPTION** **AR 728** is a viscous remover of sprayed graffiti on insensitive, porous substrates. AR 728 may be used on dry or moist substrates.
AR 728 is biologically degraded within 3 days.
- PROPERTIES** **AR 728** dissolves almost all paint sprayed onto natural and artificial stone surfaces, concrete, clinker, brickwork and rendering. AR 728 may also be applied to flat vertical surfaces when longer exposure times are necessary.
AR 728 has been allocated to Water Hazard Class 1.
- SUBSTRATE CONDITION** The substrate may be dry or moist. With absorbent substrates, in particular, intensive prewetting with water is advisable to avoid further penetration of paint pigments into the substrate.
AR 728 may be applied to surfaces protected by 2-component PU lacquer or wax to remove graffiti. The PU lacquer will not be attacked. The wax coating must normally be renewed after removal of the graffiti and neutralization.
- PROCESSING** On poorly absorbing substrates, **AR 728** is usually applied directly with a brush over the area where the graffiti are to be removed. Already after 30 to 120 sec, the paint has been sufficiently dissolved that it can be removed by water pressure or a cloth.
On absorbent substrates, intensive prewetting is advisable to prevent „graffiti shadows“. Then proceed as above.
If the graffiti could not be removed completely by the first application, the treatment should be repeated.
After successful removal of the graffiti, the substrate should be neutralized intensively with water.
It is recommended to wear goggles and butyl rubber gloves. Provide adequate fresh air. Avoid exposure to open flames.
- STORAGE** **AR 728** must be stored cool and dry and out of reach of children. Temperatures below 5° C and above 40° C must be avoided. Opened containers should be closed tightly. AR 728 has a shelf life of at least 1 year.

The information given in this technical data sheet is based upon our present knowledge and experience. Because of the wide variety of possible influences during processing and in the use of our products, it is the responsibility of the processor to carry out himself the necessary tests and trials on site. No legally binding guarantees for certain properties nor the suitability for a concrete application can be derived from the technical data sheet. Existing laws and regulations must be complied with by processors of our products on their own responsibility.

PSS INTERSERVICE U.K. LIMITED

Unit K2 Prospect Court, Prospect Close
Lowmoor Business Park
Kirkby-in-Ashfield, Notts NG17 7LF
Tel: ++44-1623-750 222
Fax: ++44-1623-723 222

<http://www.pss-technology.co.uk>
e-mail : info@pss-technology.co.uk

PSS INTERSERVICE LTD .

European Headquarter

Rebbergstr. 10
P.O. Box
CH-8954 Geroldswil
Tel: ++41-1-749 24 24
Fax: ++41-1-749 24 25

<http://www.pss-technology.com>
e-mail : info@pss-technology.com