



PSS Subito

PRODUCT INFORMATION: PSS Subito is a reversible, covering, special coating to combat graffiti and can be used in two different ways.

Application case 1: Prevention

Two coats of PSS Subito are applied as a preventive protective coating and thus act as a separating layer between the base and graffiti.

Application case 2: Covering

Graffiti is quickly and easily covered with PSS Subito. It can be used time and again for repeated graffiti attacks until the sprayer gives up and stops their activities. The best possible deterrent is achieved by painting over the fresh graffiti as soon as possible. The simple application means that one bucket kept in stock is often enough to achieve this effect.

In both cases the layers of graffiti and PSS Subito can be removed together with water.

Note: PSS Subito is not a normal facade coating, weathering and chalking can occur prematurely under heavy loads. By treating the dried PSS Subito paint with FACEAL OLEO this phenomenon will be reduced or even eliminated and the durability of the paint will be prolonged.

SUBSTRATES: PSS Subito can be used on all common plaster bases and adherent façade coatings.

PRODUCT CHARACTERISTICS:

- reversible, can be removed with water without damaging the substrate
- water vapour permeable, $s_d < 0,03 \text{ m}$
- good adhesion
- low tension, even if a number of layers are applied
- light-fast
- mineral matt
- economical, thanks to easy application
- economical since only one removal after a number of graffiti attacks
- reversible bonding agent with mineral fillers and inorganic pigments
- white, neutral-grey (colour 9526) and colours of PSS-Palette exclusiv
- Tinting concentrates 9001 to 9010 are available

APPLICATION: **Application case 1: Prevention**

Apply two coats of PSS Subito to the clean, dry substrate or dry paint coat. The priming coat can be diluted with a max. of 10% water, the finishing coat should be applied undiluted. Allow a minimum drying time of 12 hours between individual coats.

Application case 2: Covering

PSS Subito can be applied by brush or roller on the graffiti covered surface. One coat is usually enough.

The covering can be carried out in the same way a number of times if the graffiti damage is repeated.

Do not apply at temperatures below 5°C

- REMOVAL:** Wet well beforehand with water and wash off all existing layers down to the original paint coat after approx. 10-30 minutes with clear water and brush. Alternatively use a hot water pressure washing at an appropriate setting, whereby the surfaces still have to be wetted and left beforehand.
- In case of very dense or large-area graffiti, the surface can be pretreated with a thin coat of biodegradable Dispersion remover, either over the entire surface of parts thereof.
- The mixture of diluted PSS Subito and graffiti residues should be collected and disposed of in accordance with local regulations.
- CONSUMPTION:** Application case 1, Prevention:
for a two coat system, approx. 0,3 l/m²
Application case 2, Covering:
for a one coat system, approx. 0,15 l/m²
- (The consumption rate is intended for guideline purposes only and is quoted for smooth rendered surfaces. Project specifications should be referred to for specific rates.)
- CLEANING TOOLS:** Clean thoroughly with water after every stage of work.
- PACKING:** Buckets of 15 litres and 5 litres
1 litre drum (for tinting concentrates 9001 to 9010 only)
- STORAGE:** Store cool and safe from freezing in a tightly closed buckets. Shelf life: 12 months.
- IDENTIFICATION REF
ORDINANCE OF
DANTEROUS MATERIAL:** Not applicable
- PRODUCT CODE:** M-DF 01
- DANGER CLASS IN
GOODSTRAFFIC:** Not applicable
- SAFETY INSTRUCTIONS:** Protect surfaces which are not to be painted (e.g. glass, natural stone, ceramic, etc.) by suitable measures. Wash off splashes on surrounding surfaces immediately with water. Protect eyes and skin against splashes. Keep out of the reach of children.
- Observe the general rules of building technology. Subject to changes in the interests of product and application improvements. This edition replaces all former editions.

The information given in this technical data sheet is based upon our present knowledge and experience. Because of the wide variety of possible influences during processing and in the use of our products, it is the responsibility of the processor to carry out himself the necessary tests and trials on site. No legally binding guarantees for certain properties nor the suitability for a concrete application can be derived from the technical data sheet. Existing laws and regulations must be complied with by processors of our products on their own responsibility.

PSS INTERSERVICE U.K. LIMITED

Unit K2 Prospect Court, Prospect Close
Lowmoor Business Park
Kirkby-in-Ashfield, Notts NG17 7LF
Tel: ++44-1623-750 222
Fax: ++44-1623-723 222

<http://www.pss-technology.co.uk>
e-mail : info@pss-technology.co.uk

PSS INTERSERVICE LTD .

European Headquarter

Rebbergstr. 10
P.O. Box
CH-8954 Geroldswil
Tel: ++41-1-749 24 24
Fax: ++41-1-749 24 25

<http://www.pss-technology.com>
e-mail : info@pss-technology.com